

Chemical Compatibility Guide - Molded Polyethylene

For UltraTech Spill Containment Products

This listing was prepared to provide guidance to the chemical compatibility of UltraTech Spill Containment Products which are manufactured and constructed of a molded polyethylene.

Polyethylene is susceptible to attack by some chemicals which may cause stress cracking, swelling, oxidation or may permeate the polyethylene. These reactions may reduce the physical properties of polyethylene.

When considering an UltraTech polyethylene product for use in secondary containment applications, it is important to note that most secondary containment products are designed to hold leaked chemicals for only hours, a day, at most a week.

These secondary containment units would then be cleaned of any chemical. In these short term applications, a greater variety of chemicals may be used with the polyethylene since the exposure time of the chemical to the polyethylene is limited.

A = Suitable for long term storage at 100 degrees Fahrenheit or less.

B = Suitable for short term storage less than one year.

C = Do NOT store these chemicals in UltraTech containment products.

User testing may prove some of these chemicals are suitable for secondary containment applications with an exposure time of one week or less.

Aqua RegiaC

Acetaldehyde (40%)A
Acetanide
Acetic Acid (50%)A
Acetic Acid (50%)
Acetic Ether
Acetone
Acetylene Tetrabromide
Acrylic EmulsionsB
AcrylonitrileA
Adipic AcidA
Aliphatic HydrocarbonsA
AlkalineA
Allvl Alcohol (96%)A
Aluminum Chloride (20%)A
Aluminum FluorideA
Aluminum Hydrogen Solution (10%)A
Aluminum HydroxideA
Alums (All Types)A
Ammonia (Aqueous)A
Ammonium AcetateA
Ammonium BifluorideA
Ammonium Carbonate (50%)A
Ammonium ChlorideA
Ammonium Hydrogen Fluoride (50%)A
Ammonium HydroxideA
Ammonium Metaphsophate Sat'dA
Ammonium Nitrate Sat'dA
Ammonium Persulfate Sat'dA
Ammonium PhosphateA
Ammonium SaltsA
Ammonium Sulfate Sat'dA
Ammonium Sulfide, Sat'dA
Ammonium Thiocyanate Sat'dA
Amyl AcetateA
Amyl Alcohol (100%)A
Amyl ChlorideC
Aniline (100%)B
Aniline HydrochlorideB
Anti Freeze
Antimony SaltsA
Antimony Trichloride (90%)A

Aqua RegiaC
Aqueous Alkalies (NaOH)A
Arsenic AcidA
Barium CarbonateA
Barium ChlorideA
Barium CyanideA
Barium HydroxideA
Barium NitrateA
Barium SaltsA
Barium SulfateA
Barium SulfideA
Battery Fluid, AcidB
BenzaldehydeA
Benzene Sulfonic AcidB
BenzeneB
Benzoic AcidA
Benzyl AlcoholA
Benzyl ChloroformateA
Boric Acid ConcA
Boric Acid DiluteA
Borzx Cold Sat'dA
Bromine, LiquidC
Bromine, WaterC
BromobenzeneC
BromoformC
ButadieneA
Butanediol (100%)A
ButanolA
Butyl AcetateA
Butyl Alcohol (100%)A
Butyl PhenolC
Butylene GlycolA
Butylene LiquidC
ButyleneC
Butyric AcidA
Calcium CarbonateA
Calcium ChlorideA
Calcium HydroxideA
Calcium HypochloriteA
Calcium Nitrate (50%)A
Calcium SulfateA

Cai Doil Disutline	
Carbon Disulfide	
Carbon Monoxide	A
Carbon Tetrachloride	
Carbonic Acid (Aq. CO2)	
Caustic (Aqueous)	A
Caustic Potash Sol. (50%)	A
Caustic Soda Sol. (10%)	
Chloroacetic Acid	
Chlorobezene	
Chloroform	
Chloromethane	С
Chlorsulfonic Acid (100%)	
Chrome Alum Sat'd	
Chromic Acid (50%)	
Clycolic Acid (All Conc.)	
Copper Cyanide	
Cresylic Acid	
Crotonic Aldehyde	
Cuprous Chloride Sat'd	
Cyclohenanone	
Cyclohexane	
Cyclohexanol	
Dextrin Sat'd	
Dextrose Sat'd	
Di Isobutyl Ketone	
Dibutyl Ether	
Dibutyl Sebacate	
Dibutylphthalate	
Dichloroacetic Acid	
Dichlorobenzene, Liquid	
Dichloroethylene	
Diesel Fuel	
Diesel Oil	
Diethanolamine	
Diethyl Carbonate	
Diethylene Glycol	
Digycolic Acid (30%)	
Dimethyl Formamide	
Dimethylamine	
Dinonyl Phthalate	C

Carbon BisulfideC



Dioctyl Phthalate	C	Magnesium Hydroxide	A	Potassium Hydroxide	A
Dioxane	A	Magnesium Nitrate	A	Potassium Nitrate Sat'd	
Diphenyl Oxide	C	Magnesium Oxide	A	Potassium Perborate Sat'd	A
Disodium Phosphate	A	Magnesium Salts			
Electrolyte	A	Magnesium Sulfate		Potassium Phosphates	A
Ethanol	A	Maleic Acid	A	Potassium Sulfate	A
Ether	C	Methanol			A
Ethyl Acetate (100%)	В	Methyl Acetate	A	Propargyl Alcohol (7%)	A
Ethyl Alcohol	A	Methyl Alcohol (100%)	A	Propionic Acid (50%)	
Ethyl Butyrate	В	Methyl Amine (32%)		Propyl Alcohol	A
Ethyl Chloride		Methyl Bromide		Propylene Dichlrode (100%)	
Ethyl Ether	C	Methyl Chloride	C	Propylene Glycol	A
Ethylene Chloride	C	Methyl Ethyl Ketone	В	Propylene Oxide	A
Ethylene Chlorohydrin	A	Methyl Isobutyl Ketone	В	Pyridine	В
Ethylene Diamine	A	Methyl Isopropyl Ketone	В	Selenic Acid	
Ethylene Dichloride	C	Methyl Sulfate	A	Sewage	
Ethylene Glycol		Methyl Sulfuric Acid (All Conc.)		Silicic Acid	А
Ethylene Oxide		Methylene Chloride	C	Silver Nitrate	
Fatty Acids		Mineral Oils		Soda Ash	
Ferric Sulfate	A	Monochloroacetic Acid Ethyl Ester		Sodium Acetate Sat'd	А
Ferrous Salts	A	Monochloroacetic Acid Methyl Ester	A	Sodium Benzoate	
Ferrous Sulfate		Mowilith D	A	Sodium Bisulfate (10%)	
Fluoboric Acid		Naptha	В	Sodium Bisulfite	
Fluosilicic Acid (All Conc.)		Napthalene		Sodium Bromate	
Formaldehyde (40%)		Nicotine Dilute		Sodium Chloride	
Formamide		Nicotinic Acid		Sodium Chlorite	
Formic Acid (All Conc.)		Nitric Acid (50%)		Sodium Chromate	
Fuel Oil		Nitrobenzene		Sodium Disulfite	
Furfural (100%)		Nitrotoluene		Sodium Dithionite (10%)	
Furfuryl Alcohol		Octyl Cresol		Sodium Fluoride Sat'd	
Gallic Acid Sat'd		Oleic Acid (All Conc.)		Sodium Hydroxide Conc	
Gasoline		Oleum Conc		Sodium Hypochlorite	
Gluconic Acid (All Conc.)		Oxalic Acid (All Conc.)		Sodium Nitrate	
Glycerine		Palmitic Acid		Sodium Oxalate	
Glycol		Paraffin Emulsions		Sodium Persulfate	
Heptane		Perchloric Acid (50%)		Sodium Phosphate	
Hexane		Perchloroethylene		Sodium Sulfonates	
Hydrazone Hydrate		Petroleum Ether		Stearic Acid (All Conc.)	
Hydrobromic Acid (50%)		Petroleum		Succinic Acid (COM)	
Hydrochloric Acid (All Conc.)		Phenylhydrazine		Sulfuric Acid (98%)	
Hydrocyanic Acid Sat'd		Phosphoric Acid (All Conc.)		Sulfuric Acid, Fuming	
Hydrofluoric Acid (All Conc.)		Phosphorous (Yellow 100%)		Sulfurous Acid	
Hydrofluorisilicic Acid (All Conc.)		Phosphorous Chlorides		Sulfuryl Chloride	
Hydrogen Bromide (10%)		Phosphorous Pentoxide		Tartaric Acid Sat'd	
Hydrogen Peroxide (90%)		Photographic Solutions		Tetrachlorethylene	
Hydrogen Phosphide (100%)		Phthalic Acid (All Conc.)		Tetrachloroethane	
Hydrogen Sulfide		Phthalic Anhydride	А	Tetrahydrofurane	
Hydroiodic Acid (All Conc.)		Pickling Baths	Λ.	Tetrahydronaphthalene	
Hydroquinone		Sulfuric Acid Undersold a sid		Thionyl Chloride Titanium Salts	
Hydrosulfite (10%)		Hydrochloric Acid Picric Acid (194)			
Hydroxylamine Sulfate	A	Picric Acid (1%)		Toluene Sulfonic Acid (All Conc.)	
Hydrozine (35%)		Plating Solutions		Toluene Transformer Oil	
Hydrozine Hydrochloride		Potassium Aluminum Sulfates (50%) Potassium Bichromate		Tributylphosphate	
Hypochlorous AcidIso Octane		Potassium Borate (10%)		Trichloroacetic Acid	
				Trichloroethane	
Isopropyl Acetate		Potassium Bromide Potassium Chlorate		Trichloroethylene	
Isopropyl Alcohol		Potassium Chloride			
Isopropyl Ether Jet Fuel		Potassium Chromate		Tricresyl Phosphate Triethanolamine	
Kerosene				Trioctyl Phosphate	
Lactic Acid (All Conc.)		Potassium Cyanide Potassium Dichromate (40%)		Trisodium Phosphate Sat'd	
Lead Acetate Sat'd		Potassium Ferri Ferro Cyanide Sat'd		Turpentine Oil	
Magnesium Carbonate		Potassium Fluoride		Xylene	
ייים אות היים וויים וויי		ר טנמסטועווו רנעטו ועל	A	Ayıcıle	C



Ultra-IBC Spill Pallet Plus

Product Data Sheet

Description	A containment sump with deck surface used for storing and containing any leaks, spills or drips from Intermediate Bulk Containers (IBC's).
Part#	1157 (No Drain) / 1158 (With Drain)
Dimensions In. (mm)	62 x 62 x 28 (1,575 x 1,575 x 711)
Load Capacity UDL lb.(kg)	8,500 (3,856)
Sump Capacity gal (L)	365 (1,382)
Weight lb. (kg)	324.0 (147.0)
Forklift Access	2-Way
# per Pallet	3
Composition	Linear Low Density Polyethylene (LLDPE)
Color	Yellow
Compliance	Spill Prevention, Control and Countermeasure Act (SPCC). 40 CFR 264.175





IBC Spill Containment Comparison Guide



	IBC Spill Pallet	IBC Spill Pallet Plus	Modular IBC Spill Pallet	Steel IBC Spill Pallet	Twin IBC Spill Pallet	Hard Top IBC Spill Pallet	Twin IBC Hard Top	Modular IBC Hard Top
Part No.	1057 - No Drain 1058 - With Drain	1157 - No Drain 1158 - With Drain	1125 - 2 Tank Model 1126 - 3 Tank Model 1127 - 4 Tank Model 1128 - 5 Tank Model	1184	1140 - 1147	1162 - No Drain 1161 - With Drain	1148 - No Drain 1149 - With Drain	1165 - 2 Tank Model 1166 - 3 Tank Model 1167 - 4 Tank Model 1168 - 5 Tank Model
Drain	Optional	Optional	No	No	Optional	Optional	Optional	No
No. of IBC's	1	1	2-5	1	2	1	2	2-5
Material	Polyethylene	Polyethylene	Polyethylene	Steel	Polyethylene	Polyethylene	Polyethylene	Polyethylene
Containment Cap. (gal)	400	365	280-375	370	535	365	535	280-375
Weight Cap. (lbs)	16000	8500	9000 per pallet	5650	8000 per side	8500	8000 per side	9000 per pallet
Forkliftable	No	2-Way	No	4-Way	2-Way	2-Way	2-Way	No
Dims. (L x W) in.	58.75 x 58.75	62 x 62	Varies	57 x 57	124 1/2 x 61 5/8	64.5 x 62	128 x 67	Varies
Dims. (H) in.	33	28	8.75	35	22	96	96	79
Shipping	Truck	Truck	Truck	Truck	Truck	Truck	Truck	Truck
Color	Yellow	Yellow	Yellow	Silver	Yellow	Yellow	Yellow	Yellow
Cost	\$\$	\$	\$\$ - \$\$\$	\$	\$\$	\$\$\$	\$\$\$\$	\$\$\$\$ - \$\$\$\$\$
Advantage	Weight capacity. Gallon capacity.	Low profile. Forkliftable.	Modular. Low profile.	Won't melt in fire.	Stores two IBCs.	Outdoor containment.	Outdoor containment. Stores two IBCs.	Outdoor containment. Modular.
	fill		2 - A					



















MAINTENANCE AND CARE

UltraTech Polyethylene Spill Containment Products

- 1. There is no specific need to clean an UltraTech Spill Containment product that has not had a spill or leak as the polyethylene plastic material it is constructed from is designed to last for years in most indoor or outdoor environment. The polyethylene has a UV protective additive for prolonged outdoor exposure.
- 2. The products are rated for use in temperatures from -40° F to 160° F.
- 3. The sump area of the product should be inspected weekly for any spills or leaks. If a spill or leak is discovered, it should be cleaned up within 24 hours. If inspection shows the sump area has a crack or hole or other damage that could affect the functionality of the unit, it should be immediately removed from service.
- 4. To clean up a spill or a leak, use all safety precautions required for handling the particular chemical involved. Using a safe pumping method for the chemical involved, pump the spilled contents out of the containment sump and into a drum or container for proper disposal or reuse. If the chemical involved is not safe to pump, use absorbents or other means to remove the chemical from the containment sump safely. Dispose of any chemicals, used sorbents or other disposables in compliance with your local or federal regulations.
- 5. Once the chemical has been removed, use a sorbent mat or pad to wipe down the inside of the containment unit to remove any remaining chemical residue. Finish by washing with soap and water and allow the unit to dry before placing back into service.
- 6. The unit's grating should be cleaned of any residual chemical and cleaned with soap and water.
- 7. If the unit had a drain plug that was removed to drain off any chemical or soap/water, be sure to replace the drain plug securely.

- 8. Ultra-Spill Deck Bladder System special instructions:
 - a. Use a hand pump with a ½" diameter tube and insert the tube into the opening of the bladder from inside the Spill Deck after removing the grate.
 - b. Pump the contents of the bladder and the Spill Deck into a drum or container for proper disposal or reuse.
 - c. If there is some remaining residue inside the bladder, lift the outside end of the bladder and allow the residue to pour back into the Spill Deck sump where it can be pumped out or absorbed with sorbents.

d. Remove the bladder from the Spill Deck by uncrewing the bulkhead fitting and dispose of the bladder properly according to local and federal regulations. **DO NOT RE-**

use A BLADDER. After the Spill Deck has been cleaned up, place a new bladder into the Bladder Attachment and attach it to the Spill Deck following the instructions that accompany the replacement bladder.



Product Data Sheet

Item Number: 1160

Item Name: Ultra-Bucket Shelf • For use with Ultra-IBC Spill Pallets

Attach this shelf to your Ultra-IBC Spill Pallet for easy, mess free filling into 5-gallon buckets.

- Bucket shelf attaches directly to IBC Spill Pallet for easy filling of 5-gallon pails
- Catches leaks and drips during dispensing to keep floors dry and safe
- For more containment, shelf can be connected to main sump; optional configuration requires bulkhead fittings

SPECIFICATIONS:

Use With: Ultra-IBC Spill Containment Unit

Color: Black

Dimensions: 16" W x 19" D x 13" H

Sold as: 1 each

Weight: 9.0 lbs.

Composition: LDPE

UNSPSC: 24101907

METRIC EQUIVALENT

Dimensions: 40.6cm W x 48.3cm D x 33cm H

Weight: 4.1 kg

Disclaimers

• **Notice:** Call Technical Services at 1-800-353-1611 or visit our website at SpillContainment.com for chemical compatibility.

Product Data Sheet

Item Number: 1160

Item Name: Ultra-Bucket Shelf • For use with Ultra-IBC Spill Pallets

Attach this shelf to your Ultra-IBC Spill Pallet for easy, mess free filling into 5-gallon buckets.

- Bucket shelf attaches directly to IBC Spill Pallet for easy filling of 5-gallon pails
- Catches leaks and drips during dispensing to keep floors dry and safe
- For more containment, shelf can be connected to main sump; optional configuration requires bulkhead fittings

SPECIFICATIONS:

Use With: Ultra-IBC Spill Containment Unit

Color: Black

Dimensions: 16" W x 19" D x 13" H

Sold as: 1 each

Weight: 9.0 lbs.

Composition: LDPE

UNSPSC: 24101907

METRIC EQUIVALENT

Dimensions: 40.6cm W x 48.3cm D x 33cm H

Weight: 4.1 kg

Disclaimers

• **Notice:** Call Technical Services at 1-800-353-1611 or visit our website at SpillContainment.com for chemical compatibility.