

SEMI-ELECTRIC STRADDLE STACKER EA15D



Straddle Stacker



EA15D

Superior quality, maneuverable, compact, and durable for all your material handling applications. Ideal for small aisles and areas.

WEIGHT CAPACITY: 3300 lbs. @ 24" load center

LIFT HEIGHT: 138" (11.5 ft.)

FORK LENGTH: 45.3"

ADJUSTABLE OUTRIGGERS: 45.7" TO 59.1"

ADJUSTABLE FORKS: 8.3" TO 33.5"

MAST HEIGHT: 92"

TURNING RADIUS: 52.6"

BATTERY / CHARGER: 12V 120AH, deep cycle

maintenance-free batteries with internal direct connect 110A 110VAC

plug-in automatic 24V/15A charger (both Included)

LIFTING SPEED: 5.35 ips empty; 3.6 ips loaded

LOWERING SPEED: 3.85 ips empty; 4.4 ips loaded

DRIVE WHEELS: 9" x 3" Nylon

LOAD WHEELS: (2) 4" x 3" Nylon per outrigger

HYDRAULICS LIFTING MOTOR: 24V 1500 Watt lifting

Motor.

BRAKES: Foot Brake

OPERATOR CONTROLS: lifting, lowering, battery meter

CHASSIS AND MAST: Robotic Welding; Heavy duty steel chassis with I-beam mast for durability; Telescoping mast includes a protective steel guard.

MODEL#	MAST	LIFT HEIGHT	SERVICE WEIGHT
FA15D	92"	138."	1450





EA15D Semi-Electric Straddle Stacker

The EKKO EA15D Semi-Electric Straddle Stacker is designed with the combination of the versatility of a forklift and apallet stacker. It is ideal for loading and unloading trucks, loading docks, stock rooms, manufacturing floors and warehousing.

Made from high quality steel and components with durable quality drives to withstand any terrain, usage, impact and directional changes for the use of any application with confidence and assurance.

- Load Capacity 3300lbs.
- Raised Height 138" (11.5ft)
- o Adjustable Forks 8.3-33.5"
- Adjustable Legs 43.5-59.1"
- Fork Length 45.3"
- Power Lifting
- Manual Drive
- Adjustable Forks
- Built-in Charger 12v 120Ah
- Batteries Included
- o Ergonomic Handle
- Steel Construction
- Robotic Welding
- 3 Years Limited Warranty

Model		EA15D
Load Capacity	(lb.)	3300
Lifting height Max.	(in)	138
Load center distance	(in)	24
Fork length	(in)	45.3
Single fork width	(in)	4
Overall fork width	(in)	8-32.7
Lowered fork height	(in)	2.35
Fixed leg length	(in)	36.5
Fixed leg width, single	(in)	3.94
Adjustable legs	(in)	44.5-59.1
Turning radius	(in)	52.6
Overall length	(in)	70
Overall width max	(in)	61
Extended mast height	(in)	154
Lowered mast height	(in)	84.5
Battery Voltage	(V/Ah)	12V/120Ah
Charger	(V/A)	12V/15A
Lift Motor	(V/W)	DC 12V/1500W
Service Weight	(lb.)	1450

