


1 cu. yd.



2 cu. yd.

Model #	Capacity (cu.yd.)	Capacity (lbs.)	Power Source	Horizontal Clearance	Dump Angle	Cycle Time	Fork Pocket Size L x W x H	Distance Between Fork Pockets	Dimensions L x W x H	Weight (lbs.)
F89144	1	2,000	Forklift	85"	75°	5 sec	51 1/2 x 7 5/8 x 2 5/8"	27 3/8"	66 x 36 x 49"	577
F89143		4,000								637
F89142		6,000								725
F89141	2	2,000		88 1/2"					69 x 57 x 52"	692
F89140		4,000								781
F89139		6,000								912

Distance Between Fork Pockets is measured center to center.






- Improves safety while increasing productivity when transporting and dumping material.
- Forklift powered unit eliminates the need for manual latches, pull cords, and manipulation.
- Start & stop at any point during dumping/retracting process.
- Connect unit by attaching included quick-connect couplers to forklift auxiliary circuit.
- Secure unit to forklift using included safety chain.
- Control unit ergonomically by using convenient forklift controls.
- Leak-proof continuous solid welds.
- Assists facilities with OSHA compliance and LEAN initiatives.
- Heavy duty steel construction.
- Premium powder coat paint finish.
- Ships fully assembled, ready to use.
- Made in the U.S.A.



Step 1: Insert forks into fork pockets & secure unit using included safety chain.



Step 2: Connect quick-connect couplers to forklift auxiliary circuit.



Step 3: Operate powered hopper using convenient forklift controls.

Powered Self-Dumping Hoppers

Model #	Capacity (cu.yd.)	Capacity (lbs.)	Power Source	Steel Gauge	Dimensions L x W x H	Weight (lbs.)
F89144	1	2,000	Forklift	12	66 x 36 x 49"	577
F89143		4,000		10		637
F89142		6,000		7		725
F89141	2	2,000		12	69 x 57 x 52"	692
F89140		4,000		10		781
F89139		6,000		7		912

Optional Caster Pack: F10515A4, includes (4) 6 x 2" phenolic casters: 2 swivel, 2 rigid.